



CORPORATE HEADQUARTERS

P.O. BOX 2069. BELLINGHAM, WA U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0450 37" Drum Sander



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 15HP, three-phase motor and dual 6" sanding drums for smooth and fast sanding.
- Variable feed rate, amp gauge and emergency stop for safety and efficiency.
- Sands 9" x 36½" x 4" boards with ease!
- Four port dust system for maximum dust collection.
- Solid steel construction built for production environments—weighs 1143 lbs!

The Model G0450 37" Drum Sander is available for \$3,195.00. As with all Grizzly products, the Model G0450 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0450 37" DRUM SANDER, 15 HP 3-PHASE

Product Dimensions:

Weight..... 1143 lbs.
 Length/Width/Height..... 68 x 50-1/2 x 49 in.
 Foot Print (Length/Width)..... 45-1/8 x 28-1/2 in.

Shipping Dimensions:

Type..... Wood Slat Crate
 Content..... Machine
 Weight..... 1382 lbs.
 Length/Width/Height..... 55 x 60 x 45 in.

Electrical:

Minimum Circuit Size..... 40 amps at 220V, 25 amps at 440V
 Switch..... On/Off Emergency Stop
 Switch Voltage..... 220V
 Plug Included..... No
 Voltage Conversion Kit..... P0450753
 Phase Converter..... H3741

Motors:

Sanding

Type..... TEFC Induction
 Horsepower..... 15 HP
 Voltage..... 220/440V
 Prewired..... 220V
 Phase..... Three
 Amps..... 43/21.5A
 Speed..... 1725 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Dual Belt Drive
 Bearings..... Sealed and Lubricated

Conveyor

Type..... TEFC Induction
 Horsepower..... 1/3 HP
 Voltage..... 220/440V
 Prewired..... 220V
 Phase..... Three
 Amps..... 1.3/0.65A
 Speed..... 1175 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Belt and Chain Drive
 Bearings..... Sealed and Lubricated

Main Specifications:

Operation Information

| | |
|------------------------------|------------|
| No Of Sanding Heads..... | 2 |
| Maximum Board Width..... | 36-1/2 in. |
| Minimum Board Width..... | 2 in. |
| Maximum Board Thickness..... | 4 in. |
| Minimum Board Thickness..... | 1/16 in. |
| Minimum Board Length..... | 9 in. |
| Sanding Belt Speed..... | 2800 FPM |
| Sanding Drums Speed..... | 2800 FPM |
| Conveyor Feed Rate..... | 6 - 18 FPM |
| Sanding Belt Length..... | 138 in. |
| Sanding Belt Width..... | 6 in. |

Drum Information

| | |
|--------------------------------|--------------|
| Infeed Sanding Drum Type..... | Steel/Rubber |
| Infeed Sanding Drum Size..... | 6 in. |
| Outfeed Sanding Drum Type..... | Rubber |
| Outfeed Sanding Drum Size..... | 6 in. |

Construction

| | |
|---------------------------------|--------|
| Conveyor Belt Construction..... | Rubber |
| Body Construction..... | Steel |
| Base Construction..... | Steel |
| Paint..... | Epoxy |

Other Related Information

| | |
|-----------------------------|-------------|
| Floor To Belt Height..... | 29 - 33 in. |
| No Of Pressure Rollers..... | 5 |
| Pressure Roller Type..... | Rubber |
| Pressure Roller Size..... | 1-17/32 in. |
| Conveyor Belt Length..... | 90-1/2 in. |
| Conveyor Belt Width..... | 36-1/2 in. |
| Belt Roller Size..... | 2.67 in. |
| No Of Dust Ports..... | 4 |
| Dust Port Size..... | 4 in. |

Other Specifications:

| | |
|------------------------------|-----------------------------|
| Country Of Origin | Taiwan |
| Warranty | 1 Year |
| Serial Number Location | ID Label on the Control Box |
| Assembly Time | 25 minutes |

Features:

- Easy Access Control Panel with Load Meter
- Variable Speed Conveyor
- Advanced Dust Collection
- Hinged Hood With Gas Struts for Easy Drum Access
- Industrial Rubber Conveyor Belt (Similar to Wide Belt Sander Belts)
- State of the Art Computer Balanced Drums
- 0.020" Table Lift with 360 degree Handwheel Turn