



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0538 1/3 HP OSCILLATING SPINDLE SANDER

Product Dimensions:

Weight..... 34 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20 x 14 x 11-1/2 in.
Footprint (Length x Width)..... 20 x 14 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 36 lbs.
Length x Width x Height..... 18 x 23 x 16 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 4A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 9 ft.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 4A
Speed..... 1725 RPM
Type..... Single Phase Capacitor Start Induction
Power Transfer Direct Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Spindle Sander Info

Sanding Drum Diameters..... 3/4, 1, 1-1/2, 2, 3 in.
Sanding Drum Length..... 4-1/2 in.
Spindle Speed..... 1725 RPM
Spindle Oscillation..... 72 SPM
Stroke Length..... 5/8 in.
Table Length..... 20 in.
Table Width..... 14 in.
Table Thickness..... 1 in.
Table-to-Floor Height..... 11-3/8 in.
Spindle Shaft Diameter..... 1/2 in.
Number of Table Inserts..... 6
Included Sanding Sleeve Grit Size..... 80, 150

Construction Materials

Base..... Plastic
Table..... Particle Board with Plastic Laminate
Frame..... Plastic

Other Related Info

Number of Dust Ports..... 1
Dust Port Size..... 2-1/2 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label on Front of Machine
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Paddle On/Off Switch with Lock
- Five 4-1/2 in. Tall Sanding Drums
- Compact Size for Easy Storage
- Three 150 gr. Sleeves (3/4", 1-1/2" and 3")
- Six Table Inserts