



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1135 TRACK FEEDER W/ 4 SPEEDS, SINGLE-PHASE

Product Dimensions:

Weight..... 139 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 43-1/4 x 23-1/2 x 29-1/2 in.
Footprint (Length x Width)..... N/A x N/A

Shipping Dimensions:

Carton #1

Type..... Cardboard
Content..... Machine
Weight..... 72 lbs.
Length x Width x Height..... 30 x 12 x 23 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 78 lbs.
Length x Width x Height..... 13 x 11 x 30 in.

Electrical:

Minimum Circuit Size..... 10 amp
Switch..... Forward/Reverse with 2 Speeds
Switch Voltage..... 220V
Cord Length..... 9 ft.
Cord Gauge..... 16 gauge
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 7.7/6.2A
Speed..... 3400/1700 RPM
Cycle..... 60 Hz
Number of Speeds..... 2
Power Transfer Gear Box
Bearings..... Lubricated for Life

Main Specifications:

Workpiece Capacities

Min. WorkPiece Len..... 8 in.

Operation Info

No. Of Feed Speeds..... 4
Feed Speeds..... 14.5, 29, 39, 78 FPM
Swing..... 360 deg.
Vertical Movement..... 9-1/2 in.
Horizontal Movement..... 24-1/4 in.
Rotation..... Forward, Reverse

Roller Info

No. Of Rollers..... 5
Roller Suspension..... 3/4 in.
Max Hght Rollers Parallel Table Surface..... 8-1/2 in.

Track Info

No. Of Track Pieces..... 3
Track Width..... 1/2 in.
Track Length..... 44 in

Other

Column Diameter..... 2-1/4 in.

Construction Info

Roller..... Synthetic Rubber
Housing..... Cast Aluminum
Supports..... Cast Iron
Column..... Steel
Paint..... Epoxy

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location "Checked" Sticker, On Out-feed Portion Of Housing's Roller / Belt Cover Side
Assembly Time 45 minutes

Features:

Rollers are Spring Tensioned with 3/4" Travel
Heavy-Duty Gear Reduction with Hardened Gears
Universal Positioning with Handle Locks